



# VEDATUDO ESPUMA EXPANSIVA

EXPANSIVE POLYURETHANE FOAM

### Packaging

300 ml – 250 g  
500 ml – 340 g  
750 ml – 700 g



### Pallets

Box with 12 units

### Color

Amber

### Achievement

11 liters

### Shelf life

Valid for 12 months from the date on which it was manufactured, as long as the storage regulations are observed.

Store in a covered, dry, ventilated place, away from heat sources, in environments with a temperature not exceeding 30°C and in an upright position.

### Notes

Do not use as structural filling.

We recommend using the entire can in one day and, if the product is not used, do not remove the applicator nozzle and let a portion of foam naturally form at the tip of the nozzle.

Do not smooth the foam down, let it dry for at least 2 hours before cutting off the excess

When you wish to reuse the product, shake the can and cut the tip of the nozzle, the product must be reused within 3 days

### Description

Single-component, expansive polyurethane foam that reacts with moisture in the air to become a rigid, non-toxic foam with fastening, adhesion, insulating and filling properties after curing.

### Where to apply

- ✓ Fixing frames and tubes;
- ✓ Filling holes;
- ✓ Masonry wedging;
- ✓ General insulation;

For other applications consult our technical team **DRYKO**.

### Advantages

- ✓ Easy to apply;
- ✓ Resistant;
- ✓ Fast drying;
- ✓ Protects and insulates;
- ✓ Great adhesion;

### Technical Data

Tests	Unit	Specification
Dry to the touch (surface)	Min.	Max. 20
Total curing time	H	12

### Surface preparation

The substrate for the application of **VEDATUDO ESPUMA EXPANSIVA** must be clean, free of foreign bodies, mold remains, hardware tips, remains of release or impregnating agents, flaws and irregular aggregates.

On smooth concrete, sand with a steel brush or mechanically to increase porosity and remove release or curing agents.

### Handling and safety

[www.DRYKO.com.br](http://www.DRYKO.com.br)

DRYKO has it covered!

Rua Antônio Rodrigues Filho, 404 | Vila Aeroporto.  
Guarulhos | SP | Zip Code (CEP) 07170-325  
Phone: 11 2088-5700





# VEDATUDO ESPUMA EXPANSIVA

EXPANSIVE POLYURETHANE FOAM

- ✓ Flammable product. Keep away from heat, sources of ignition or any flames and sparks.
- ✓ Handle with care. Avoid strong impact and contact with sharp surfaces
- ✓ We recommend observing the safety standards established by the competent bodies and the use of appropriate PPE.
- ✓ The product must not be ingested or come into contact with the skin or eyes.
- ✓ In case of accidental ingestion, do not force vomiting. In contact with eyes, rinse well with water for at least 15 minutes. In contact with the skin, wash well with soap and water and use a moisturizing cream. Do not remove the product. See a doctor.
- ✓ Keep out of reach of children and animals.
- ✓ In closed places, if necessary, create forced ventilation.
- ✓ For further information on handling and safety, refer to the product MSDS, available on our website – [www.dryko.com.br](http://www.dryko.com.br).
- ✓ Dispose of content/container at an approved waste treatment and disposal plant. Do not reuse the package.

## Product application

Apply the product with the valve down, pull the trigger with two fingers. You can dose the amount of foam by tilting the trigger. Fill 1/3 of the gap, as the foam expands.

In vertical areas, apply from the bottom up. Gaps greater than 3 cm must be filled in stages and at each stage, the previously hardened layer must be moistened.

To fix door frames, apply 3 points on each side in the areas close to the hinges, with each point having approximately 30 cm of cured foam.

To fix windows, apply 8 points. The gap between the masonry and the frame must not exceed 1.5 cm.

## Cleaning

The tools and equipment can be cleaned with solvent before the product is dry and, after the product is dry, the removal must be carried out mechanically.

## LEGAL NOTICE

DRYKO IMPERMEABILIZANTES guarantees the quality of its products against manufacturing defects, according to the legal provisions of the Consumer Protection Code, pointing out that the final performance of the product is directly influenced by the quality of the application and its conditions, including factors such as climate, temperature, storage, and ways of application.

DRYKO may make changes to the products whenever it deems necessary, without prior notice.

The information on this product datasheet is based on our experience and knowledge, for guidance purposes, and in accordance with the procedures of the current standard, with laboratory analyses carried out in accordance with the requirements of the products, uses not provided for in this document will not be considered.

## Product preparation

Shake the product package well, remove the cap and screw the applicator nozzle which can be found on the cap's handle.

[www.DRYKO.com.br](http://www.DRYKO.com.br)

DRYKO has it covered!

Rua Antônio Rodrigues Filho, 404 | Vila Aeroporto.  
Guarulhos | SP | Zip Code (CEP) 07170-325  
Phone: 11 2088-5700

